

# Marlborough - Blenheim LiDAR 1m DSM (2014)

## Metadata

### File Identifier

CB2B9184-96DB-4A66-904D-BAAC3FBEB52A

### Language

eng

### Character Set

#### Character Set Code

utf8

### Hierarchy Level

#### Scope Code

dataset

### Hierarchy Level Name

dataset

## Contact

### Responsible Party

#### Organisation Name

LINZ - Land Information New Zealand

#### Position Name

Lidar Coordination Manager

### Contact Info

#### Contact

##### Phone

###### Telephone

###### Voice

04 4600110

##### Address

###### Address

###### Delivery Point

155 The Terrace

###### City

Wellington

###### Postal Code

6145

###### Country

New Zealand

###### Electronic Mail Address

info@linz.govt.nz

### Role

#### Role Code

pointOfContact

## Date Stamp

### Date

2018-12-06

## Metadata Standard Name

ANZLIC Metadata Profile: An Australian/New Zealand Profile of AS/NZS ISO 19115:2005, Geographic information - Metadata

## Metadata Standard Version

1.1

## Reference System Info

## Reference System

### Reference System Identifier

#### Identifier

##### Code

2193

## Identification Info

### Data Identification

#### Citation

##### Citation

##### Title

Marlborough - Blenheim LiDAR 1m DSM (2014)

##### Date

### Abstract

This layer contains the DSM for LiDAR data from Blenheim, the Wairau valley region and lower Awatere river corridor captured in 2014. - The DEM is available as layer [Marlborough - Blenheim LiDAR 1m DEM (2014)](<http://data.linz.govt.nz/layer/95483-marlborough-blenheim-lidar-1m-dem-2014/>). - The index tiles are available as layer [Marlborough - Blenheim LiDAR Index Tiles (2014)] (<http://data.linz.govt.nz/layer/95576-marlborough-blenheim-lidar-index-tiles-2014/>). - The LAS point cloud and vendor project reports are available from [OpenTopography] (<http://opentopo.sdsc.edu/datasets>). Lidar was captured for Marlborough District Council by New Zealand Aerial Mapping in February and May 2014. The datasets were generated by New Zealand Aerial Mapping and their subcontractors. Data management and distribution is by Land Information New Zealand. Data comprises: - DEM: tif or asc tiles in NZTM2000 projection, tiled into a 1:1,000 tile layout - DSM: tif or asc tiles in NZTM2000 projection, tiled into a 1:1,000 tile layout - Point cloud: las tiles in NZTM2000 projection, tiled into a 1:1,000 tile layout Pulse density specification is 1.4 pulses/square metre in open ground. Vertical datum is NZVD2016.

### Status

#### Progress Code

completed

### Point Of Contact

#### Responsible Party

##### Organisation Name

LINZ - Land Information New Zealand

##### Position Name

Lidar Coordination Manager

#### Contact Info

##### Contact

##### Phone

##### Telephone

##### Voice

04 4600110

##### Address

##### Address

##### Delivery Point

155 The Terrace

##### City

Wellington

##### Postal Code

6145

##### Country

New Zealand

##### Electronic Mail Address

info@linz.govt.nz

#### Role

##### Role Code

pointOfContact

## Resource Maintenance

Maintenance Information  
Maintenance And Update Frequency  
Maintenance Frequency Code  
notPlanned

Resource Format  
Format  
Name  
\*.xml  
Version  
Unknown

Descriptive Keywords  
Keywords  
Keyword  
New Zealand  
Type  
Keyword Type Code  
theme

Thesaurus Name  
Citation  
Title  
ANZLIC Jurisdictions  
Date  
Edition  
Version 2.1  
Edition Date  
Date  
2008-10-29  
Identifier  
Identifier  
Code  
<http://asdd.ga.gov.au/asdd/profileinfo/anzlic-jurisdic.xml#anzlic-jurisdic>  
Cited Responsible Party  
Responsible Party  
Organisation Name  
ANZLIC the Spatial Information Council  
Role  
Role Code  
custodian

Resource Constraints  
Security Constraints  
Classification  
Classification Code  
unclassified

Resource Constraints  
Legal Constraints  
Use Limitation  
Copyright in this work is owned by Marlborough District Council © Marlborough District Council  
Use Constraints  
Restriction Code  
copyright

Resource Constraints  
Legal Constraints  
Use Limitation  
Released by LINZ under Creative Commons Attribution 4.0 New Zealand (CC BY 4.0) with:  
Following Attribution: "Sourced from the LINZ Data Service and licensed by Marlborough

District Council, for re-use under CC BY 4.0." For details see:  
<https://www.linz.govt.nz/data/licensing-and-using-data/attributing-elevation-or-aerial-imagery-data>

Use Constraints  
Restriction Code  
license

Spatial Representation Type Code  
grid

Representative Fraction  
Denominator  
Integer  
1000

Language  
eng

Character Set  
Character Set Code  
utf8

Topic Category Code  
elevation

Extent  
EX\_ Extent  
Geographic Element  
EX\_ Geographic Description  
Identifier  
Authority  
Citation  
Title  
ANZMet Lite Country codelist

Date

Edition  
Version 1.0

Edition Date  
Date  
2009-03-31

Identifier  
Identifier  
Code  
<http://asdd.ga.gov.au/asdd/profileinfo/anzlic-country.xml#Country>

Cited Responsible Party  
Responsible Party  
Organisation Name  
ANZLIC the Spatial Information Council

Role  
Role Code  
custodian

Code  
nzl

Data Quality Info  
DQ\_ Data Quality  
Scope  
DQ\_ Scope  
Level  
Scope Code  
dataset

Level Description  
Scope Description  
Other

## Lineage

LI\_Lineage  
Statement

Survey Specification: -Scanner: Optech Sensor -Flying Height: 900m above lowest ground - Scan Angle:  $\pm 20$  degrees -Scan Frequency: 40Hz -Pulse Rate: 70 or 75kHz -Points Per M2: 1.4

Data Acquisition: The LiDAR was acquired between 23 to 28 February 2014 and on 3 May 2014 using NZAM's Optech LiDAR sensor systems. The data in the tidal influence area was collected within 2 hours either side of low tide. The data was collected flying 900 metres above lowest ground, and using a scan angle of 20 degrees either side of nadir. The outgoing laser pulse rate (PRF) was set at either 70kHz or 75kHz and mirror scan frequency 40 Hz. The settings were selected to create a dataset with a minimum 1.4 point per square meter pulse density in open ground. New Zealand Aerial Mapping used a reference mark we established at Woodbourne (NZAM0161) for the collection of GNSS base station data during the aerial data acquisition. Independent of the aerial survey work Sounds Surveying Ltd field surveyed a series of topographic features in open ground, to be later used to verify the accuracy of the processed ground dataset. This field survey work was conducted between 10 and 13 March 2013. The field survey work is in terms of LINZ geodetic marks AB83, AD84, BE0G, AD5R, A3TV, B3ED, A7GH, BAK6, A867, ACYW, APW4 and BH3D. Data processing: The LiDAR sensor positioning and orientation (POS) was determined using the acquired GPS/IMU datasets and Applanix POSPac software. This work was all undertaken in NZGD2000 geodetic reference system using the data collected at the LINZ geodetic reference marks for the differential processing. The POS data was combined with the LiDAR range files and used to generate LiDAR point clouds in NZTM map projection. This process was undertaken using Optech LiDAR Mapping Suite software. As well as creating the point clouds this software also checks the relative fit between points in the individual swath overlap areas. All subsequent data processing steps were undertaken using TerraSolid's LiDAR processing software modules TerraScan and TerraModeler. The point cloud was checked for completeness of project coverage and pulse density. Automated routines tailored to the projects land cover and terrain were then setup and run on the data to create a ground classified point cloud. This data was converted from ellipsoidal heights to Nelson 1955 vertical datum using the LINZ NZGeoid09 grid and offset model. Comprehensive manual editing of the LiDAR point cloud data was undertaken to improve the quality of the automatically classified ground point dataset. This editing involved visually checking over the data and changing the classification of points into and out of the ground point dataset. As part of this process LiDAR returns from water bodies were removed from the ground point dataset and supplementary points were added to help support hydro flow characteristics around and along water bodies. The positional accuracy of the processed data has been checked by overlaying the Sounds Surveying field surveyed features on the LiDAR dataset displayed with its intensity values. The data was found to fit well in position. The height accuracy of the classified ground points were checked by calculating height difference statistics between a TIN of the LiDAR ground points and the field surveyed points. The standard deviation statistic for the data is  $\pm 0.06$ m. The data from New Zealand Aerial Mapping was supplied in NZTM map projection and the Nelson 1955 vertical datum, the point cloud datasets had been tiled into NZTopo50 1:2000 tiles. Classification of the point cloud followed the classification scheme below: 1 - Unassigned 2 - Ground 14 - Above\_Ground

Data Reprocessing: In 2017 the data was reprocessed by AAM New Zealand for LINZ relative to the NZVD2016 vertical datum, NZGD2000 horizontal datum, NZTM map projection, with the NZGeoid2016. This data was supplied as 1:1000 nominal scale (720m high x 480m wide tiles per full NZ Topo50 sheet). Sounds Surveying Ltd undertook ground surveying to support the original work. For this project, the Sounds Survey converted this dataset to NZVD2016. When doing so, they took accord of any local adjustments to geodetic marks that had been applied to the original field surveying coordinates. Classification of the point cloud followed the classification scheme below: 2 - Ground 14 - Non Ground

The starting point for processing was the Classified point clouds produced for Marlborough DC based on NZGeoid09. This data has been reverted to ellipsoidal heights, then NZGeoid2016 has been applied to convert the data to orthometric heights. The data was then compared to the ground surveying NZVD2016 test points, and an appropriate final Z shift applied to each block. Ground point data had been checked to check site data obtained by the field survey, this was assumed to be error free. The test points were distributed across the mapping area and located on clear open ground. Difference statistics yielded for Reference Project Site Awatere: RMS 0.035m and for Wairau: RMS 0.045m All point attribute data (intensity, return number, GPS time) in the original data points have been imported into the new las file dataset. Lakes and large rivers were hydroflattened in the bare earth digital elevation model. The deliverables to LINZ were: 1m gridded bare earth digital elevation model (DEM) 1m gridded digital surface model (DSM) Classified point cloud

Classified point cloud Data hosted by OpenTopography was re-classified: the Above\_Ground (14) points were reclassified as Unassigned classification (1)

Metadata Constraints

Legal Constraints

Use Limitation

Copyright of this work is owned by Land Information New Zealand © LINZ

Use Constraints

Restriction Code

copyright

Metadata Constraints

Legal Constraints

Use Limitation

Released by LINZ under Creative Commons Attribution 4.0 International (CC BY 4.0) with:  
Following Attribution: "Sourced from the LINZ Data Service and licensed for reuse under CC BY  
4.0" For details see <https://www.linz.govt.nz/data/licensing-and-using-data/attributing-linz-data>

Use Constraints

Restriction Code

license